## REVOLUTION IN COMPRESSOR HEAT RECOVERY











#### Effective R&D department

We have an effective research and development department that focuses on the continuous improvement of its energy efficiency products and services. This enables us to offer the latest technologies and innovative solutions to achieve optimal efficiency and energy savings. The R&D department also collaborates with top manufacturers of air compressors and HVAC equipment to implement cutting-edge solutions. Our entire team is involved in researching and developing sustainable solutions in line with the latest green standards.

### 25 years of experience in HVAC (Heating, Ventilation & Air Conditioning)

With more than 25 years of track record in HVAC, our company provides the highest quality service to our customers. With industry-leading technologies and a team of experienced engineers and technicians, we are able to successfully integrate powERpack and powERcontrol products into heating or processes across a variety of industry sectors. We also hold a firm commitment to sustainability, ensuring that our innovative solutions comply with the latest green standards.





# Innovation leader in compressor heat recovery

We are at the forefront of innovation in compressor heat recovery. By advancing innovative solutions, we have developed equipment that allows for the most efficient recovery of heat generated by industrial compressors on the market. This allows energy to be reused in production processes or for heating, leading to energy cost savings and promoting green initiatives such as reducing the CO2 footprint. All solutions developed by our company comply with the latest standards and technical requirements.





Innovative and most advanced compressor heat recovery module.

powERpack is a revolutionary product developed as part of an R&D project in partnership with the National Centre for Research and Development (NCBR). At the heart of the powERpack lies innovative compressor heat recovery technology, tested in rotary screw and vane compressors in almost 6,000 measurement runs across the full temperature range.

The developed mathematical models of the physical properties of the compressors provide a solid foundation for the safe and efficient recovery of heat in performance heating parameters.

The most effective control algorithm for heat recovery has been selected out of 21 control methods in almost 2,000 measurement runs. This allows the powERpack to recover heat efficiently, with a well-documented heat exchange efficiency of more than 90%. On top of this, the powERpack guarantees the lowest oil-side pressure drop in its class! With powERpack, users of industrial air compressors save on energy costs and protoct the environment while improving the efficiency of their heating

and protect the environment while improving the efficiency of their heating systems. A prime example of how innovative technological solutions can make a positive impact on our lives and the environment.







ER)CONTROL POW(

Innovative hydraulic module for heat recovery from compressors with integrated heat exchanger

### COMPRESSOR OPERATION SAFETY GUARANTEED

#### RANGE UP TO 110 kW!



A controller with a touchscreen control panel is responsible for implementing the most effective control algorithm for compressor heat recovery. It allows the entry of the desired receiving temperature and protects the compressor from overheating and overcooling. On top of this, it monitors the operating status of the actuators and has a built-in Ethernet interface. The controller also calculates the amount of heat energy received.

Oil fittings - a system adapted from the marine industry far exceeding the rigour of temperature and pressure found in air compressors.

Tested in almost 4,000 measurement runs, the heat exchanger delivers the lowest pressure drop in its class. Rated compressor cooling quality guaranteed, even in the absence of heat recovery.





Oil-side bypass valve arrangement - the exchanger can be shut down on the fly of compressor operation.

Readings from the water-side and oil-side temperature sensors enable control of the heat recovery process to ensure efficiency and safety.

The variable-speed pump is a control and actuation element that primarily ensures the safe yet efficient extraction of heat from the compressor oil, adapting to the current operating conditions of the compressor and the receiving side.

RANGE UP TO 500 kW!



Forms a compressor heat recovery system for compressors with an integrated heat exchanger.

A controller with a touchscreen control panel is responsible for implementing the most effective control algorithm for compressor heat recovery. It allows the entry of the desired receiving temperature and protects the compressor from overheating and overcooling. On top of this, it monitors the operating status of the actuators and has a built-in Ethernet interface. The controller also calculates the amount of heat energy received.

Readings from the water-side and oil-side temperature sensors enable control of the heat recovery process to ensure efficiency and safety.





Integrated shut-off valves and check valve.

The variable-speed pump is a control and actuation element that primarily ensures the safe yet efficient extraction of heat from the compressor oil, adapting to the current operating conditions of the compressor and the receiving side.





POWERPACK RANGE								
Model	Compressor power (kW)	Dimensions mm (L x W x H)	Disposable pressure water side	Electric power				
PP30	30	920/480/730	60 kPa	<300W				
PP75	75	920/480/730	50 kPa	<300W				
PP110	110	920/480/730	50 kPa	<300W				









## POWERCONTROL RANGE

Model	Compressor power (kW) for Δ15/Δ20	Pump module dimensions mm (L x W x H)	Control unit dimensions mm (L x W x H)	Disposable pressure water side	Electric power
PC55	55	420/250/230	300/300/200	60 kPa	<300W
PC110	110	920/250/230	300/300/200	50 kPa	<300W
PC160	132/200	920/245/280	300/300/200	40 kPa	<300W
PC250	200/300	920/245/280	300/300/200	40 kPa	<300W
PC350	250/350	920/245/280	300/300/200	40 kPa	<300W
PC500	350/500	920/245/280	300/300/200	40 kPa	<300W



environment





asfi



